

# Alfa Laval AQ6L

# Gasketed plate heat exchanger for HVAC applications

#### Introduction

Alfa Laval AlfaQ<sup>™</sup> is AHRI Certified® through the Liquid to Liquid Heat Exchangers (LLHE) Certification Program which ensures thermal performance in accordance with the product specifications.

The relatively tall plate makes this model suitable for duties with long temperature programs and when high heat recovery is appreciated. A large range of plate and gasket types is available.

#### **Applications**

• HVAC

#### **Benefits**

- High energy efficiency low operating cost
- Flexible configuration heat transfer area can be modified
- Easy to install compact design
- High serviceability easy to open for inspection and cleaning and easy to clean by CIP
- Access to Alfa Laval's global service network

#### Features

Every detail is carefully designed to ensure optimal performance, maximum uptime and easy maintenance. Selection of available features, depending on configuration some features may not be applicable:





- Corner guided alignment system
- Reinforced hanger
- Chocolate pattern distribution area
- Clip-ad gasket
- Offset gasket groove
- Leak chamber
- Bearing boxes
- Fixed bolt head
- Key hole bolt opening
- Lifting lug
- Lining
- Lock washer
- Pressure plate roller
- Tightening bolt cover



#### Alfa Laval 360° Service Portfolio

Our extensive service offering ensure top performance from your Alfa Laval equipment throughout its life cycle. The Alfa Laval 360 Service Portfolio include installation services, cleaning and repair as well as spare parts, technical documentation and trouble shooting. We also offer replacement, retrofit, monitoring and much more.


For information about our complete service offering and how to contact us - please visit www.alfalaval.com/service.


## General remarks for technical information

- The global offering presented in this leaflet may not be available for all regions
- All combinations may not be configurable

## **Dimensional drawing**

Measurements mm (inches)





Туре	Н	W	h
TL15-FM	2752 (108.3")	610 (24.0")	342 (13.5")
TL15-FG	2752 (108.3")	637 (25.1")	342 (13.5")
TL15-FG, ASME	2752 (108.3")	646 (25.4")	342 (13.5")
TL15-FD, ASME	2752 (108.3")	646 (25.4")	342 (13.5")
TL15-FG	2752 (108.3")	646 (25.4")	342 (13.5")
TL15-FS, ASME	2752 (108.3")	646 (25.4")	342 (13.5")

## Technical data

Туре

Plates

TL15-B	Single plate	1.9 (0.075)
Materials		
Heat transfer plates		304/304L, 316/316L
		Ti
Field gask	ets	NBR, EPDM
Flange connections		Carbon steel
		Metal lined: stainless steel, titanium
		Rubber lined: NBR, EPDM
Frame and pressure plate		Carbon steel, epoxy painted

Free channel, mm (inches)

Other materials may be available on request

## Operational data

Frame, PV-code	Max. design pressure (barg/psig)	Max. design temperature (°C/°F)
FM, pvcALS	10.0/145	180/356
FG, pvcALS	20.0/290	200/392

Max. design pressure (barg/psig)	Max. design temperature (°C/°F)
10.3/150	250/482
20.0/290	200/392
20.7/300	250/482
35.0/507	200/392
31.7/460	250/482
35.0/507	200/392
	(barg/psig) 10.3/150 20.0/290 20.7/300 35.0/507 31.7/460

Extended pressure and temperature rating may be available on request.

### Flange connections

Frame model	Connection standard
	EN 1092-1 DN150 PN10
FM, pvcALS	ASME B16.5 Class 150 NPS 6
	JIS B2220 10K 150A
	EN 1092-1 DN150 PN16
	EN 1092-1 DN150 PN25
FG, pvcALS	ASME B16.5 Class 150 NPS 6
	JIS B2220 10K 150A
	JIS B2220 16K 150A
FG, ASME	ASME B16.5 Class150 NPS 6
	EN 1092-1 DN150 PN16
FG, PED	EN 1092-1 DN150 PN25
	ASME B16.5 Class 150 NPS 6
FD, ASME	ASME B16.5 Class 300 NPS 6
FDc, ASME	
	EN 1092-1 DN150 PN25
	EN 1092-1 DN150 PN40
FS, pvcALS	ASME B16.5 Class 400 NPS 6
	JIS B2220 10K 150A
	JIS B2220 20K 150A
FS, ASME	ASME B16.5 Class 400 NPS 6
	EN 1092-1 DN150 PN25
FS, PED	EN 1092-1 DN150 PN40
	ASME B16.5 Class 400 NPS 6

Standard EN1092-1 corresponds to GOST 12815-80 and GB/T 9115.

## Certificates



This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval Corporate AB. No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval Corporate AB's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

CHE00102-2-EN-GB © Alfa Laval Corporate AB